

Multispectral Camera

8-Band Visible

Our 8-band visible multispectral camera incorporates a high performance CMOS sensor that is modified with Spectral Devices proprietary pixelated filter array technology. This versatile camera simultaneously captures images at 8 distinct bands at full frame rate. No need for additional filters, filter wheels, or tunable filters. All spectral information is captured simultaneously by the multispectral sensor. Our visible multispectral camera has 8 bands of spectral discrimination spaced between 474 nm and 640 nm. The camera is USB3 Vision-compliant offering many software choices including graphical, command-line, Matlab, and LabView applications. SDKs are available for Windows and Linux operating systems. Power is supplied through the USB3 interface. Compact, lightweight, and designed for demanding visible imaging applications.



FEATURES:

- Snapshot Operation
- High Frame Rate
- Compact and Lightweight
- Capture Bands Simultaneously
- High Performance CMOS Sensor
- Low Power Requirement
- 474, 495, 526, 546, 578, 597, 621, 640 nm
- USB3 Vision & GenICam Compliant
- 28 mounting points

SPECIFICATIONS:

- Lens Mount: C-mount
- Interface: USB3 Vision
- Maximum Bit Depth: 12 bit
- Shutter: Global Shutter
- Sensor Type: CMOS
- Capture Method: Area
- Sensor Model: CMV4000
- Sensor Format: 1-inch
- Number of Channels: 8 bands
- Pixels Per Channel: 256 x 256
- Pixel Size (H x V): 5.5 x 16.5 (μm)
- Dynamic Range: 60 dB
- Dark Noise: 13 e⁻ (RMS)
- Dark Current: 125 e⁻/s (25° C)
- Power Requirement: USB 3.0 interface
- Size: 56 mm x 50 mm x 52 mm (WxHxD)
- Weight: 200 g
- Case: 6061 Aluminium
- 12 x ¼-20 mounting points
- 12 x M3 mounting points
- 4 x 4-40 mounting points
- Compatible with 30 mm cage optics

